UNDERBODY CYLINDER


TYPE: A DWR - DOUBLE

SERIE : Ø 130

CYL.TYPE A DWR 4.1220.130 - D.150

For Tipping Weight See Advices Below

Technical Characteristics



Cylinder stages

Ø Stage	Ø045	Ø060	Ø076	Ø092	Ø108	Ø069	Ø088	Ø107	Ø126	Ø145	Ø165	Ø167	Ø187	Ø210	Ø236	Ø265
Thrust at 250 Bar [Tons]		7.10	11.3	16.60	22.90											
Stages of cylinder																

Specifications

Stages number	1	04
Cylinder Stroke	[mm]	1220
Cylinder weight only	[Kgs]	38
Working volume	[Ltrs]	7.0
Max Working pressure	[Bar]	250

Technical information

□ Oil	: See oil specification sheet
☐ Tipping weight	: Net weight body + Payload

Components

Pin Ø36/50x520 – R=310 Fil.M36x3	PL_36-520	6.30 [Kgs] x 1 =
Nut M36x3 H.40 PF Zn.B.	DDA#F36BB	0.40 [Kgs] x 2 =
Complete cradle x A DWR Double 130	M02000	49.3 [Kgs] x 1 =

Recommendation

- ☐ This Binotto cylinder is designed as a lifting device only
- ☐ It must not be used as a structural member or be subject to side loads
- ☐ Pump flow in consultation with Binotto engineering department

Advices

All our cylinders are manufactured to suit the particular application in the differing world markets/climate. Should you require details of the exact lifting capacity of the cylinder that has been selected for your application/vehicle then please contact our technical department who will be only pleased to explain or advise.

BINOTTO SRL

BINOTTO IS CONSTANTLY ENGAGED IN IMPROVING ITS PRODUCTS AND THEREFORE RESERVES THE RIGHT TO MODIFY WITHOUT ANY NOTICE CHARACTERISTICS SHOWN VIA DIVISIONE JULIA, 7/B - 36031 DUEVILLE [VI] ITALY • TEL. 0039.0444.593290 - FAX. 0039.0444.593357 • E-MAIL. INFO@BINOTTO.COM

Edit.: 04 • 2006 Rev.: 01 • 2006 Date: 01.09.2006

Pag.: A DWR 4.1220.130_01