



| Stage diameter [mm] | Thrust at 150 bar [ton] |
|---------------------|-------------------------|
| 145 | 24.7 |
| 126 | 18.7 |
| 107 | 13.5 |
| 088 | 9.2 |
| 069 | 5.6 |
| | |
| | |
| | |
| | |

| Cylinder Description | Ø Stages [mm] | | | | | | | | | Stroke [mm] | E [mm] | R [mm] | Ø Ball [mm] | Capacity [Lt] | Weight [Kg] |
|----------------------|---------------|-----|-----|----|----|----|-----|------|----|-------------|--------|--------|-------------|---------------|-------------|
| | I | II | III | IV | V | VI | VII | VIII | IX | | | | | | |
| B DWR 5/1025/ 168 | 145 | 126 | 107 | 88 | 69 | | | | | 1025 | 415 | 186 | 60 | 11.5 | 50 |
| B DWR 5/1125/ 168 | | | | | | | | | | 1125 | 435 | 209 | | 12.3 | 53 |
| B DWR 5/1225/ 168 | | | | | | | | | | 1225 | 455 | 227 | | 13.3 | 55 |
| B DWR 5/1325/ 168 | | | | | | | | | | 1325 | 475 | 245 | | 14.4 | 57 |
| B DWR 5/1425/ 168 | | | | | | | | | | 1425 | 495 | 263 | | 15.4 | 59 |
| B DWR 5/1525/ 168 | | | | | | | | | | 1525 | 515 | 282 | | 16.5 | 62 |
| B DWR 5/1725/ 168 | | | | | | | | | | 1725 | 555 | 320 | | 18.5 | 67 |
| B DWR 5/2000/ 168 | | | | | | | | | | 2000 | 615 | 378 | | 20.9 | 75 |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |

ACCESSORIES

| Cradle | | Brackets | | Turn adapters | |
|--------|--|----------|-------|---------------|--|
| CUL#AE | | SU#CC | SU#AB | RSN#90ABXBC0 | |