



\* For loads over 30000 kg, request ball with Ø 80

Stage diameter [mm]	Thrust at 125 bar [ton]
265	68.9
236	54.7
210	43.3
187	34.3
165	26.7
145	20.6
126	15.6
107	11.2
088	7.6

Cylinder Description	Ø Stages [mm]									Stroke [mm]	E [mm]	R [mm]	Ø Ball [mm]	Capacity [Lt]	Weight [Kg]
	I	II	III	IV	V	VI	VII	VIII	IX						
B DWR 9/1795/ 300	265	236	210	187	165	145	126	107	88	1795	455	266	68	49.1	172
B DWR 9/1975/ 300										1975	475	282		53.9	181
B DWR 9/2155/ 300										2155	495	298		58.7	190
B DWR 9/2335/ 300										2335	515	315		63.5	198
B DWR 9/2515/ 300										2515	535	332		68.3	205
B DWR 9/2695/ 300										2695	555	349		73.1	216
B DWR 9/3055/ 300										3055	595	384		82.6	230
B DWR 9/3575/ 300										3575	655	439		95.8	261

**ACCESSORIES**

Cradle		Brackets		Turn adapters	
CUL#CQ			SU#AE	RSN#90ADXBD0	RSN#00ADXAD1